

BNPM/LTE/CPHWT /323/2019-20	BANK NOTE PAPER MILL INDIA PRIVATE LIMITED	Cover Sheet
	CORRIGENDUM NO. 1 Supply of Centrifugal Pump with Accessories for Hot Water Transfer at BNPM Plant, Mysuru	Sheet 1 of 4

**CORRIGENDUM NO. 1 DATED 12.07.2019**

**FOR**

**TENDER No.**

**BNPM/LTE/CPHWT/323/2019-20 DATED 03.07.2019**

**FOR**

**Supply of Centrifugal Pump with Accessories for Hot Water Transfer at BNPM Plant, Mysuru**

**PURCHASER : BANK NOTE PAPER MILL INDIA PRIVATE LIMITED**

**EQUIPMENT : CENTRIFUGAL PUMP WITH ACCESSORIES**

**LOCATION : BNPM PLANT, MYSURU, KARNATAKA**



**ISSUE  
R1**

BNPM/LTE/CPHWT /323/2019-20	BANK NOTE PAPER MILL INDIA PRIVATE LIMITED	Cover Sheet
	<b>CORRIGENDUM NO. 1</b> <b>Supply of Centrifugal Pump with Accessories for Hot Water Transfer at BNPM Plant, Mysuru</b>	Sheet 2 of 4

**1.0 SCOPE OF THIS CORRIGENDUM**

1. Details provided in this corrigendum shall override those mentioned in the tender no. BNPM/LTE/CPHWT/323/2019-20 Dated: 03.07.2019

2. Except for details mentioned herein, all other details contained in the tender no. BNPM/LTE/CPHWT/323/2019-20 Dated: 03.07.2019 shall remain unchanged.

**3. Due date of bid submission:**

Closing date and time for receipt of tenders	25.07.2019; 1430 Hrs.
Time and date of opening of techno-commercial bid	25.07.2019; 1500 Hrs.

**4. Inclusions/Clarifications through this corrigendum:**

Sl. No.	As per Tender Clause	Action/Clarification incorporated in this Corrigendum
	Please refer Next Page	Please refer Next Page



BNPM/LTE/CPHWT /323/2019-20	BANK NOTE PAPER MILL INDIA PRIVATE LIMITED	Cover Sheet
	CORRIGENDUM NO. 1 Supply of Centrifugal Pump with Accessories for Hot Water Transfer at BNPM Plant, Mysuru	Sheet 3 of 4

<p><b>Section VII:</b> <b>Technical Specifications:</b></p> <p><b>Scope of Work:</b></p> <p>1 Supply of Centrifugal Pump with Accessories for Hot Water Transfer (Page no. 31 of 48)</p>	<table border="1"> <thead> <tr> <th>Sl.no.</th> <th>Parameters</th> <th>Specification</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Pump Type</td> <td>Centrifugal</td> </tr> <tr> <td>2</td> <td>Head</td> <td>46 - 48 m WC</td> </tr> <tr> <td>3</td> <td>Flow</td> <td>42 – 45 m3/hr.</td> </tr> <tr> <td>4</td> <td>Liquid</td> <td>Hot Water @85degC</td> </tr> <tr> <td>5</td> <td>Impeller MOC</td> <td>CF8M; SS (Corrosion Resistant)</td> </tr> <tr> <td>6</td> <td>Casing MOC</td> <td>Cast Iron</td> </tr> <tr> <td>7</td> <td>Shaft MOC</td> <td>SS (Corrosion Resistant)</td> </tr> <tr> <td>8</td> <td>Suction</td> <td>Horizontal</td> </tr> <tr> <td>9</td> <td>Discharge</td> <td>Vertical</td> </tr> <tr> <td>10</td> <td>Make:</td> <td>KSB/KIRLOSKAR/SULZER/Equivalent approved by BNPM</td> </tr> <tr> <td colspan="3">Accessories to be supplied by along with the Pump</td> </tr> <tr> <td>11</td> <td colspan="2">Base Frame for Complete Pump Assembly (MOC Mild Steel)</td> </tr> <tr> <td>12</td> <td colspan="2">Anchor bolts for base frame anchoring</td> </tr> <tr> <td>13</td> <td colspan="2">Coupling with following description Type: Elastomer Coupling Make: Rexnord Model: Rex Viva / Rex Omega Size: Suitable for above Pump</td> </tr> <tr> <td>14</td> <td colspan="2">Coupling Guard</td> </tr> <tr> <td>15</td> <td colspan="2">Drive Motor: Rating : 3-phase squirrel cage motor suitable for above pump Make: Siemens/ BBL /ABB/ CGL Only.</td> </tr> </tbody> </table>	Sl.no.	Parameters	Specification	1	Pump Type	Centrifugal	2	Head	46 - 48 m WC	3	Flow	42 – 45 m3/hr.	4	Liquid	Hot Water @85degC	5	Impeller MOC	CF8M; SS (Corrosion Resistant)	6	Casing MOC	Cast Iron	7	Shaft MOC	SS (Corrosion Resistant)	8	Suction	Horizontal	9	Discharge	Vertical	10	Make:	KSB/KIRLOSKAR/SULZER/Equivalent approved by BNPM	Accessories to be supplied by along with the Pump			11	Base Frame for Complete Pump Assembly (MOC Mild Steel)		12	Anchor bolts for base frame anchoring		13	Coupling with following description Type: Elastomer Coupling Make: Rexnord Model: Rex Viva / Rex Omega Size: Suitable for above Pump		14	Coupling Guard		15	Drive Motor: Rating : 3-phase squirrel cage motor suitable for above pump Make: Siemens/ BBL /ABB/ CGL Only.	
	Sl.no.	Parameters	Specification																																																	
	1	Pump Type	Centrifugal																																																	
	2	Head	46 - 48 m WC																																																	
	3	Flow	42 – 45 m3/hr.																																																	
	4	Liquid	Hot Water @85degC																																																	
	5	Impeller MOC	CF8M; SS (Corrosion Resistant)																																																	
	6	Casing MOC	Cast Iron																																																	
	7	Shaft MOC	SS (Corrosion Resistant)																																																	
	8	Suction	Horizontal																																																	
	9	Discharge	Vertical																																																	
	10	Make:	KSB/KIRLOSKAR/SULZER/Equivalent approved by BNPM																																																	
	Accessories to be supplied by along with the Pump																																																			
	11	Base Frame for Complete Pump Assembly (MOC Mild Steel)																																																		
	12	Anchor bolts for base frame anchoring																																																		
13	Coupling with following description Type: Elastomer Coupling Make: Rexnord Model: Rex Viva / Rex Omega Size: Suitable for above Pump																																																			
14	Coupling Guard																																																			
15	Drive Motor: Rating : 3-phase squirrel cage motor suitable for above pump Make: Siemens/ BBL /ABB/ CGL Only.																																																			



BNPM/LTE/CPHWT /323/2019-20	BANK NOTE PAPER MILL INDIA PRIVATE LIMITED	Cover Sheet
	<b>CORRIGENDUM NO. 1</b> <b>Supply of Centrifugal Pump with Accessories for Hot Water Transfer at BNPM Plant, Mysuru</b>	Sheet 4 of 4

Sl.no.	Technical Description	Bidder Compliance* Yes/No/Deviation
1	Pump Type: Centrifugal	
2	Head: 46-48 m WC	
3	Flow: 42-45 m3/hr.	
4	Liquid: Hot Water @85degC	
5	Impeller MOC: CF8M; SS (Corrosion Resistant)	
6	Casing MOC: Cast Iron	
7	Shaft MOC: SS (Corrosion Resistant)	
8	Suction: Horizontal	
9	Discharge: Vertical	
10	Offered Make: KSB/KIRLOSKAR/SULZER/Equivalent approved by BNPM	
Accessories to be supplied by along with the Pump		
11	Base Frame for Complete Pump Assembly (MOC Mild Steel)	
12	Anchor bolts for base frame anchoring	
13	Coupling with following description Type: Elastomer Coupling Make: Rexnord Model: Rex Viva / Rex Omega Size: Suitable for above Pump	
14	Coupling Guard	
15	Drive Motor: Rating : 3-phase squirrel cage motor suitable for above pump Make: Siemens/ BBL /ABB/ CGL Only.	

**Section VII:  
Quality Control Requirements:**

We will supply the material strictly as per specifications and compliance statements given below.

Deviation from the above mentioned technical details to be provided in the below tabular Column for the offered products  
(Page no. 32 of 48)

2

