

BNPM/OTE/SI/0190/20 22-23	BANK NOTE PAPER MILL PRIVATE LIMITED	SHEET 1 OF 1
	SUPPLY OF SLIP ON FLANGE CORRIGENDUM NO. 2	

CORRIGENDUM No. 2, DATED 18.07.2022

FOR

e-TENDER NO. BNPM/OTE/SOF/0190/2022-23 DATED 21.06.2022

SUPPLY OF SLIP ON FLANGE

CLIENT : BANK NOTE PAPER MILL INDIA PRIVATE LIMITED

PROJECT : 12000 TPA BANK NOTE PAPER MILL AT MYSORE

LOCATION : MYSORE, KARNATAKA



**BANK NOTE PAPER MILL INDIA PRIVATE LIMITED
NOTE MUDRAN NAGAR
MYSORE 530005**

ISSUE
R0

BNPM/OTE/SI/0190/20 22-23	BANK NOTE PAPER MILL PRIVATE LIMITED		SHEET 1 OF 1
	SUPPLY OF SLIP ON FLANGE CORRIGENDUM NO. 2		

1.0 SCOPE OF THIS CORRIGENDUM

1.1 This corrigendum dated 12.07.2022, is issued for extension of bid submission date for tender floated on 21.06.2022

1.2 Except for details mentioned herein, all other details contained in the tender no. BNPM/OTE/SOF/0190/2022-23 dated 21.06.2022, shall remain applicable and unchanged.

2.0 REVISION TO THE TENDER:-

2.1 Clause no. 1.0 is revised as

Closing date and time for submission of bids
along with supporting documents through E-tendering 26.07.2022, 1400 hrs
portal.

Opening date and time 26.07.2022, 1430 hrs

2.2 Amendment to Technical Specification (Enclosed flange chart):-

S. No	Tender Reference	Technical Specification per tender	as Amendment to Technical Specification
1	Section VII- Technical Specification, Page No : 34 of 56, SI No. a) Section VIII- Quality Control Requirements, Page No : 35 of 56, SI No. 1)	DIN : 305 Bolt Size : 24	DIN : 350 Bolt Size : 20
2	Section VII- Technical Specification, Page No : 34 of 56, SI No. b) Section VIII- Quality Control Requirements, Page No : 35 of 56, SI No. 2)	Bolt Size : 20	Bolt Size : 24

ISSUE
R0

Technical information

Flange standards

Ti-916 EN

Edition: 2019-08

DN mm	PN 10				PN 16				PN 25				PN 40				PN 63				PN 100				Class 150				Class 300				Class 600				DN in.
	Flange Yd	B.c.d. Hcd	Bolt size	No. of bolts	Flange Yd	B.c.d. Hcd	Bolt size	No. of bolts	Flange Yd	B.c.d. Hcd	Bolt size	No. of bolts	Flange Yd	B.c.d. Hcd	Bolt size	No. of bolts	Flange Yd	B.c.d. Hcd	Bolt size	No. of bolts	Flange Yd	B.c.d. Hcd	Bolt size	No. of bolts	Flange Yd	B.c.d. Hcd	Bolt size	No. of bolts	Flange Yd	B.c.d. Hcd	Bolt size	No. of bolts					
25	115	85	12	4	115	85	12	4	115	85	12	4	115	85	12	4	140	100	16	4	140	100	16	4	108	79.4	1/2	4	124	88.9	5/8	4	124	88.9	5/8	4	1
40	150	110	16	4	150	110	16	4	150	110	16	4	150	110	16	4	170	125	20	4	170	125	20	4	127	98.4	1/2	4	156	114.3	3/4	4	156	114.3	3/4	4	1.5
50	165	125	16	4	165	125	16	4	165	125	16	4	165	125	16	4	180	135	20	4	195	145	24	4	152	120.7	5/8	4	165	127	5/8	8	165	127	5/8	8	2
65	185	145	16	8	185	145	16	8	185	145	16	8	185	145	16	8	205	160	20	8	220	170	24	8	178	139.7	5/8	4	191	149.2	3/4	8	191	149.2	3/4	8	2.5
80	200	160	16	8	200	160	16	8	200	160	16	8	200	160	16	8	215	170	20	8	230	180	24	8	191	152.4	5/8	4	210	168.3	3/4	8	210	168.3	3/4	8	3
100	220	180	16	8	220	180	16	8	235	190	20	8	235	190	20	8	250	200	24	8	265	210	27	8	229	190.5	5/8	8	254	200	3/4	8	273	215.9	7/8	8	4
125	250	210	16	8	250	210	16	8	270	220	24	8	270	220	24	8	295	240	27	8	315	250	30	8	254	215.9	3/4	8	279	235	3/4	8	330	266.7	1	8	5
150	285	240	20	8	285	240	20	8	300	250	24	8	300	250	24	8	345	280	30	8	355	290	30	12	279	241.3	3/4	8	318	269.9	3/4	12	356	292.1	1	12	6
200	340	295	20	8	340	295	20	12	360	310	24	12	375	320	27	12	415	345	33	12	430	360	33	12	343	298.5	3/4	8	381	330.2	7/8	12	419	349.3	1/8	12	8
250	395	350	20	12	405	355	24	12	425	370	27	12	450	385	30	12	470	400	33	12	505	430	36	12	406	362	7/8	12	445	387.4	1	16	508	431.8	1 1/4	16	10
300	445	400	20	12	460	410	24	12	485	430	27	16	515	450	30	16	530	460	33	16	585	500	39	16	483	431.8	7/8	12	521	450.9	1 1/8	16	560	488.9	1 1/4	20	12
350	505	460	20	16	520	470	24	16	555	490	30	16	580	510	33	16	600	525	36	16	655	560	45	16	533	476.3	1	12	584	514.4	1 1/8	20	605	527.0	1 3/8	20	14
400	565	515	24	16	580	525	27	16	620	550	33	16	660	585	36	16	670	585	39	16	715	620	45	16	597	539.8	1	16	648	571.5	1 1/4	20	685	603.2	1 1/2	20	16
450	615	565	24	20	640	585	27	20	670	600	33	20	685	610	36	20	715	630	39	20	770	675	45	20	635	577.9	1 1/8	16	711	628.7	1 1/4	24	745	654.0	1 5/8	20	18
500	670	620	24	20	715	650	30	20	730	660	33	20	755	670	39	20	800	705	45	20	870	760	52	20	699	635	1 1/8	20	775	685.8	1 1/4	24	815	723.9	1 5/8	24	20
600	780	725	27	20	840	770	33	20	845	770	36	20	890	795	45	20	930	820	52	20	990	875	56	20	813	749.3	1 1/4	20	914	812.8	1 1/2	24	940	838.2	1 7/8	24	24
700	895	840	27	24	910	840	33	24	960	875	39	24	995	900	45	24									927	863.6	1 1/4	28								28	
800	1015	950	30	24	1025	950	36	24	1085	990	45	24	1140	1030	52	24									1060	977.9	1 1/2	28								32	
900	1115	1050	30	28	1125	1050	36	28	1185	1090	45	28													1168	1086	1 1/2	32								36	
1000	1230	1160	33	28	1255	1170	39	28	1320	1210	52	28																									
1200	1455	1380	36	32	1485	1390	45	32																													

¹ According to EN 1092-2 (Cast iron flanges) and EN 1092-3 (Copper alloy flanges), the flanges in this DN and PN may be supplied with 4 holes. Where steel flanges are required with 4 holes, these may be supplied by agreement between manufacturer and purchaser.

Color-coded fields show which flange standards have the same dimensions for each DN size.

